

FilterMart™ LG LIQUID/GAS COALESCER ELEMENT

FMC # 19-0333



Performance Data

Micron Rating: 0.30 ABSOLUTE

Beta Rating: N/A

Collapse Pressure Rating: 75 PSID

Maximum Temperature: 180 F

Direction of Flow: INSIDE->OUT

Recommended Changeout Differential Pressure: 15 PSID

Additional Notes: EQUIV. FOR PALL #CC3LGA7H13. 500 SCFM @100 F.& 100 PSIG

Dimensional Specifications

(A) Outer Diameter, Top: 2.75 IN (69.85 MM)

(B) Outer Diameter, Bottom: 2.75 IN (69.85 MM)

(C) Inner Diameter, Top: 1.56 IN (39.62 MM)

(D) Inner Diameter, Bottom:

(E) Length: 30.00 IN (762.00 MM)

(F) Thread: NONE

Physical Specifications

Handle: NONE

Seal Material: BUNA-N

Type of Adhesive: EPOXY

Type of Endcap: POLYPROPYLENE

Center Tube: CARBON STEEL

Type of Media: BOROSILICATE

Filter Area: SQ.IN.

Plating: NONE

Outer Jacket: YES

Configuration: SINGLE OPEN END

Packaging Specifications

Number per Carton: 4

Carton Weight: 10.00 LB (4.54 KG)